

## SAFE-D Fire-Rated Fixings: Cable Compatibility Guide



Includes EV  
cable fixings  
& EV-Ultra  
Guide!




**Having invented the first fire-rated clips that could be fixed to substrates or in PVC trunkings, D-Line acknowledge how cable management can literally be a matter of life and death in fire conditions, requiring an uncompromising approach to installations.**

We offer innovative ranges made in the UK and fire-rated, to satisfy regulatory and best practice requirements. Our Safe-D range has been designed with technical features and installer benefits that deliver outstanding value and quality.

For specifiers, distributors, and installers, please use this Guide to identify the right Safe-D clip for your installation. Should you require any further information, please never hesitate to contact us. We'll always be delighted to be of service.

**Best Always,  
D-Line Team**



### Safe-D Range



- Stag clips, single and twin
- Wrap and lock Conduit saddles
- Wrap and lock adjustable cable clips
- F-Clips
- U-Clips
- Spring Clips
- Retro Clips
- D-Fixing screws
- Drill bits
- T&E grip clips
- EV fixing packs

**Exova**  
Warringtonfire



**20**  
YEARS OF  
INNOVATION  
IN CABLE  
MANAGEMENT

## Stag Clips

D-Line Solution	Cable Diameter (mm)	Popular Cable Usages	Partcodes		
	6-8mm single	1.5mm 2c+E FP 0.75mm 3183Y 0.75mm 3184Y 1mm 3182Y 1mm 3183Y 1mm 6242Y 1.5mm 6242Y	SAFEDSTAG6S/50 SAFEDSTAG6SR/50 SAFEDSTAG6SB/50	Galv Red Black	
	8-10mm single	1.5mm 2c+E Enhanced 2.5mm 2c+E FP 1.5mm 3c+E FP 1mm 4c+E FP 1.5mm 4c+E FP 1.5mm 4c+E Enhanced 2.5mm 2c+E Enhanced 1.5mm 3183Y 2.5mm 6242Y 1.5mm 3183AG	SAFEDSTAG8S/50 SAFEDSTAG8SR/50 SAFEDSTAG8SB/50	Galv Red Black	
	6-8mm twin	As single 6-8mm above, but all x2	SAFEDSTAG6T/50 SAFEDSTAG6TR/50 SAFEDSTAG6TB/50	Galv Red Black	
	8-10mm twin	As single 8-10mm above, but all x2	SAFEDSTAG8T/50 SAFEDSTAG8TR/50 SAFEDSTAG8TB/50	Galv Red Black	

Caution; when containing mains cables in conduits and trunkings, 50% of internal capacity should be free for air circulation. Cable diameters can vary according to different manufacturers' tolerances. We advise checking cables for compatibility.










## Adjustable Cable Clips & Conduit Saddles

D-Line Solution	Cable Diameter	Popular Cable Usages	Partcodes
	10-17mm	XLPE 1.5mm 2c, 1.5mm 3c, 1.5mm 4c, 1.5mm 5c / 1.5mm 7c XLPE 2.5mm 2c, 2.5mm 3c, 2.5mm 4c, 2.5mm 5c XLPE 4mm 2c, 4mm 3c 4mm 2c+E FP, 4mm 3c, 4mm 4c+E FP, 2.5mm 3c Enhanced, 2.5mm 4c Enhanced , 4mm 3c Enhanced, 4mm 4c Enhanced 4mm 3c SY 4mm 4c SY 4mm 5c SY	SD-CAB10/20 Galv SD-CAB10B/20 Black
	16-21mm	XLPE 1.5mm 12c XLPE 2.5mm 5c XLPE 2.5mm 7c XLPE 4mm 4c XLPE 6mm 4c XLPE 10mm 2c XLPE 10mm 4c XLPE 16mm 2c XLPE 25mm 2c 20mm conduits, pipes & hoses	SD-CAB16/20 Galv SD-CAB16B/20 Black
	22-26mm	XLPE 16mm 4c XLPE 1.5mm 27c 25mm 3c XLPE 25mm 4c XLPE 25mm conduits, pipes & hoses	SD-CAB22/20 Galv SD-CAB22B/20 Black
	20mm	20mm rigid conduits/pipes (plastic and galvanised finish)	SAFE-DCOND20/20 Galv SAFE-DCOND20W/20 White SAFE-DCOND20B/20 Black
	25mm	25mm rigid conduits/pipes (plastic and galvanised finish)	SAFE-DCOND25/20 Galv SAFE-DCOND25W/20 White SAFE-DCOND25B/20 Black













Caution; when containing mains cables in conduits and trunkings, 50% of internal capacity should be free for air circulation. Cable diameters can vary according to different manufacturers' tolerances. We advise checking cables for compatibility.

# U-Clips & F-Clips

D-Line Solution	Popular Cable Usages	Partcodes
	<p>2x 1.5mm 2c+E FP Enhanced                  2x 1mm 6242Y                  2x 1.5mm 6242Y                  2x 2.5mm 6242Y                  2x 1.5mm 2c+E FP                  2x 1mm 3182Y                  2x 1mm 3183Y                  Inside 25x16mm trunking; D-Line Mini 30x15mm trunking</p>	<p>SAFE-D30/100</p> 
	<p>10x 1.5mm 6242Y                  6x 2.5mm 6242Y                  5x 4mm 6242Y                  4x 6mm 6242Y                  2x 10mm 6242Y                  2x 16mm 6242Y                  6x 1.5mm 3c+E FP                  5x 1.5mm 4c+E FP                  6x 1.5mm 2c+E FP Enhanced                  6x 1.5mm 3c+E FP Enhanced                  5x 1.5mm 4c+E FP Enhanced                  5x 2.5mm 2c+E FP Enhanced                  Inside 38mm or 40mm PVC trunkings; D-Line Maxi 50x25mm trunking                  6x 1mm 3184Y                  5x 1.5mm 3183Y                  4x 1.5mm 3184Y                  3x 1.5mm 3185Y                  3x 2.5mm 3183Y                  3x 2.5mm 3184Y                  6x CW1308 1mm 10 PAIR                  5x CW1308 1mm 12 PAIR                  6x 1.5mm 3183AG                  5x 1.5mm 3184AG                  3x 2.5mm 3183AG                  3x 2.5mm 3184AG                  3x 4mm 3184AG</p>	<p>SAFE-D40/50</p> 
	<p>15x 1.5mm 6242Y                  10x 2.5mm 6242Y                  7x 4.0mm 6242Y                  6x 6.0mm 6242Y                  8x 1.5mm 2c+E FP Enhanced                  8x 1.5mm FP 2c+E                  8x 2.5mm FP 2c+E                  Inside 50mm PVC trunkings</p>	<p>SAFE-D50/50</p> 
	<p>Capacity generally as U-Clip 30, 40, 50 &amp; guides though differences are possible by alternative shaping possibilities.</p>  <p>Note F40 and F50 versions have lockable tabs, for added security.</p>	<p>SAFEDFLCIP30/100                  SAFEDFCLIP40/50                  SAFEDFCLIP50/50</p> 

Caution; when containing mains cables in conduits and trunkings, 50% of internal capacity should be free for air circulation. Cable diameters can vary according to different manufacturers' tolerances. We advise checking cables for compatibility.

## Spring Clip & T&E Grip Clips

D-Line Solution	Popular Cable Usages	Partcodes
	2x 1.5mm 2c+E FP 2x 1.5mm 2c+E Enhanced 2x 0.75mm 3183Y 2x 0.75mm 3184Y 3x 1.5mm 6242Y 2x 2.5mm 6242Y 2x 1.5mm 6243Y 1x 4mm 6242Y 1x 6mm 6242Y 3x 0.75mm 2182Y 3x 0.75mm 2183Y 3x 1mm 3182Y 2x 0.75mm 3183Y 2x 1mm 3183Y Inside 10mm or 16mm PVC trunkings	SAFEDSPRING/50 
	1x 1.5mm flat T&E	SD-TE1.5/100 
	1x 2.5mm flat T&E	SD-TE2.5/100 
	1x 4.0mm flat T&E	SD-TE4.0/100 
	1x 6.0mm flat T&E	SD-TE6.0/100 

Caution; when containing mains cables in conduits and trunkings, 50% of internal capacity should be free for air circulation. Cable diameters can vary according to different manufacturers' tolerances. We advise checking cables for compatibility.

## Also Available



### Safe-D D-Fixing screws

- Compliant with BS7671 and BS5839-1 requirement
- Non-corrosive finish
- No need for plastic wall plugs
- Excellent tensile strength, and pull-out load performance



### Safe-D Retro Clips

- 5mm eyelet for screw-fixing - make compliance visible
- Will not drop to cause potentially fatal cable entanglements
- Simply fit 1x screw via 5mm eyelet
- Labour saving - 1 fixing only

Product Code	Number and nominal CSA of conductors	Approx. overall diameter	D-Line Product
EV-ULTRA3C4.0CAT5	3 x 4.0mm <sup>2</sup> + Cat5e FTP	14.8mm	EVFIX10B
EV-ULTRA3C4.0CAT5SWA	3 x 4.0mm <sup>2</sup> + Cat5e FTP	16.5mm	EVFIX10B/EVFIX16B
EV-ULTRA3C6.0CAT5	3 x 6.0mm <sup>2</sup> + Cat5e FTP	16.0mm	EVFIX10B/EVFIX16B
EV-ULTRA3C6.0CAT5SWA	3 x 6.0mm <sup>2</sup> + Cat5e FTP	18.6mm	EVFIX16B
EV-ULTRA3C710CAT5	3 x 10.0mm <sup>2</sup> + Cat5e FTP	17.6mm	EVFIX16B
EV-ULTRA3C710CAT5SWA	3 x 10.0mm <sup>2</sup> + Cat5e FTP	20.2mm	EVFIX16B
EV-ULTRA3C716CAT5	3 x 16.0mm <sup>2</sup> + Cat5e FTP	20.0mm	EVFIX16B
EV-ULTRA3C716CAT5SWA	3 x 16.0mm <sup>2</sup> + Cat5e FTP	22.5mm	CAB22B
EV-ULTRA5C6.0CAT5	5 x 6.0mm <sup>2</sup> + Cat5e FTP	17.9mm	EVFIX16B
EV-ULTRA5C6.0CAT5SWA	5 x 6.0mm <sup>2</sup> + Cat5e FTP	20.5mm	EVFIX16B
EV-ULTRA5C710CAT5	5 x 10.0mm <sup>2</sup> + Cat5e FTP	19.8mm	EVFIX16B
EV-ULTRA5C710CAT5SWA	5 x 10.0mm <sup>2</sup> + Cat5e FTP	23.4mm	CAB22B


**Use CAB10B 10>17mm cable dia**

**Use CAB16B 16>21mm cable dia**

**Use CAB22B 22>26mm cable dia**

- Wrap & lock clips
- Tight fitment, stylish design
- No visible drill hole, hidden screw-fixing
- Secure screw fix, no wall plug required

**Screw-fix, locate cable, wrap & lock**



**18th Edition Compliant**



THE QUEENS AWARDS FOR  
ENTERPRISE: 3X WINNERS  
FOR INNOVATION AND  
INTERNATIONAL TRADE

