




D-Line 50x25mm Maxi is a versatile trunking, providing capacity for several cables.

The size, capacity and range of colours makes this profile a market-leading solution that is ideal for many AV, electrical and datacoms projects.

- Unique stylish 'D-Line' appearance
- Saves channelling walls
- Self-adhesive, or can be drilled & screw-fixed (as recommended for best practice)
- Accessories for perfect finish



Production method	Single piece design, produced in one single process by extrusion
PVC base & lid	Light weight, easy to handle & cut Self-extinguishing Can be drilled
Flexible hinge	Effectively bonds base & lid - lid cannot detach Impact absorbing Can be opened & closed thousands of times
Available colours	White, Magnolia, Black, Aluminium Effect, Oak Effect
UV stabilised	Will not discolour or turn brittle in sunlight
Operating temperature	Stable between -30°C up to +60°C
½ round design	No sharp edges Enables subtle aesthetics Blends above skirting
External dimensions	50mm x 25mm (W x H)
Tape	Foam backed 1mm thick Effective on clean dry surfaces Caution, can spoil surfaces on removal
Paintable	Scuff using gentle abrasive such as sandpaper, so paint keys for best results
Weight	0.27 kg per metre
Packaging	Each length supplied with removable film cover
Capacity	If containing 240v cords leave 45% of internal capacity for air circulation
Quality approvals	BS EN 50085 - 1:2005 Part 1 SGS Registration ELS 185841/2/C/AB/16



D-Line 60x30mm Maxi+ provides a useful option when extra capacity is required for multiple cables.

60 x 30 mm profiles are popular for containing HDMI and aerial cables dropping from wall mounted TV's... scaling very well for example with 50" + width screens.

The effective adhesive backing can be useful as a fixing guide, then – same as all D-Line trunking – the lengths can be drilled for screw-fixing also.

- Unique stylish 'D-Line' appearance
- Patented hinge & click-lock lid
- Paintable
- 'Easy to install, looks great!'
- Self-adhesive
- Fully safety tested and certified to BS EN 50085-1:2005

Production method	Single piece design, produced in one single process by extrusion
PVC base & lid	Light weight, easy to handle & cut Self-extinguishing Can be drilled
Flexible hinge	Effectively bonds base & lid - lid cannot detach Impact absorbing Can be opened & closed thousands of times
Available colours	White, Magnolia, Black, Aluminium Effect
UV stabilised	Will not discolour or turn brittle in sunlight
Operating temperature	Stable between -30°C up to +60°C
½ round design	No sharp edges Enables subtle aesthetics Blends above skirting
External dimensions	60mm x 30mm (W x H) - Our largest profile!
Tape	Foam backed 1mm thick Effective on clean dry surfaces Caution, can spoil surfaces on removal
Paintable	Scuff using gentle abrasive such as sandpaper, so paint keys for best results
Weight	0.39 kg per metre
Capacity	If containing 240v cords leave 45% of internal capacity for air circulation Can contain up to 8+ popular TV cables
Quality approvals	BS EN 50085 - 1:2005 Part 1 SGS Registration ELS 185841/2/C/AB/16