

1/4-Round Trunking 22mm x 22mm



1/4-round 22 x 22mm profile covers expansion gaps between floors and skirting. The 22 x 22mm (W x H) dimensions scale well to blend with popular skirting boards, while providing capacity for cable bending radii around corners.


Traditional floor trim is usually nailed, and requires perfect measuring of lengths before corners can be mitre-cut at 45° angles. By contrast D-Line 1/4-round can simply peel-and-stick to skirting, while the Clip-Over corner-bends save any need for precise measuring and can cover oblique cuts.

Compared to regular floor trim, D-Line features combine to enable approximately 50% quicker installations – and then it's easy to add or remove cables!

- Easy to install, looks great!
- Self-adhesive, simply peel & stick to skirting
- Clip-Over or Smooth-Fit corners eliminate the need to mitre-cut
- A smart alternative to traditional floor trims
- Shock-absorbing hinge effect
- A neat cornice option also (see pic above)
- Fully safety tested and certified to BS EN 50085-1:2005

Code	Description	Colour
R2D22QSW	(L) 2m x (W) 22mm x (H) 22mm	White
R3D22QSW	(L) 3m x (W) 22mm x (H) 22mm	White
R2D22QSO	(L) 2m x (W) 22mm x (H) 22mm	Oak Effect
R2D22QSP	(L) 2m x (W) 22mm x (H) 22mm	Stainable Wood
R2D22QSF1	(L) 2m x (W) 22mm x (H) 22mm	Light Oak Effect

¼-Round Trunking 22mm x 22mm



Product Specification

Production method • Single piece design, produced in one single process by extrusion

PVC base & lid • Light weight, easy to handle & cut - lid cannot detach
• Self-extinguishing
• Can be drilled

Elastomer hinge • Effectively bonds base & lid
• Impact absorbing
• Can be opened & closed thousands of times

Available colours • White • Oak Effect • Stainable • Light Oak Effect

UV stabilised • Will not discolour or turn brittle in sunlight

Operating temperature • Stable between -30°C upto +60°C

¼ round design • No sharp edges
• Enables subtle aesthetics
• For horizontal (& vertical) 90 degree intersections

External dimensions • 22mm x 22mm (w x h)

Popular usages • Covers expansions gaps around floor edges
• Indoors as Floor Trim; for Worktops; Corner drops

Tape • Foam backed 1mm thick
• Effective on clean dry surfaces
• Caution, can spoil surfaces on removal

Paintable • Scuff using gentle abrasive such as sandpaper, so paint keys for best results

Weight • 0.15 kg per metre

Packaging • Each length supplied with removable film cover

Capacity • If containing 240v cords leave 45% of internal capacity for air circulation

Quality approvals • BS EN 50085 - 1:2005 Part 1