



## Mini Trunking 30mm x 15mm














D-Line 30x15mm Mini Trunking offers a subtle appearance to make surface cable installations look attractive! The ½-round shape can blend to resemble the natural top-section of skirting boards, while offering a modern solution for vertical cable drops and runs across ceilings.

Available in a variety of colours that can blend with surrounds or create a striking visual feature. This versatile profile is popular for 2x 2.5mm T&E, 2x 1.5mm 2c FP cables, 2x broadband cable and 4x Cat-5 combinations.

- Unique stylish 'D-Line' appearance
- Patented hinge & click-lock lid
- Self-adhesive
- Paintable
- Clip-Over & Smooth-Fit accessories for perfect finish
- 'Easy to install, looks great!'
- Adaptors enable popular connections
- Fully safety tested and certified to BS EN 50085-1:2005

| Code | Description  | Colour         | Code                 | Description  | Colour         |
|------|--|----------------|----------------------|--|----------------|
|      | (L) 2m x (W) 30mm x (H) 15mm<br>(L) 3m x (W) 30mm x (H) 15mm | White<br>White | R2D3015B<br>R3D3015B | (L) 2m x (W) 30mm x (H) 15mm<br>(L) 3m x (W) 30mm x (H) 15mm | Black<br>Black |
|      | (L) 2m x (W) 30mm x (H) 15mm<br>(L) 3m x (W) 30mm x (H) 15mm |                | R2D30150<br>R3D30150 | (L) 2m x (W) 30mm x (H) 15mm<br>(L) 3m x (W) 30mm x (H) 15mm |                |
|      | (L) 2m x (W) 30mm x (H) 15mm<br>(L) 3m x (W) 30mm x (H) 15mm |                | R3D3015R             | (L) 3m x (W) 30mm x (H) 15mm                                 | Red            |

## Mini Trunking 30mm x 15mm





## **Product Specification**

| Production method     | <ul> <li>Single piece design, produced in one single process by extrusion</li> </ul>  |  |  |  |
|-----------------------|---|--|--|--|
| PVC base & lid        | <ul> <li>Light weight, easy to handle &amp; cut - lid cannot detach</li> <li>Self-extinguishing</li> <li>Can be drilled</li> </ul>    |  |  |  |
| Elastomer hinge       | <ul> <li>Effectively bonds base &amp; lid</li> <li>Impact absorbing</li> <li>Can be opened &amp; closed thousands of times</li> </ul> |  |  |  |
| Available colours     | • White • Magnolia • Black • Aluminium Effect • Wood Effect • Red   |  |  |  |
| UV stabilised         | • Will not discolour or turn brittle in sunlight  |  |  |  |
| Operating temperature | • Stable between -30°C upto +60°C   |  |  |  |
| ½ round design        | <ul> <li>No sharp edges</li> <li>Enables subtle aesthetics</li> <li>Blends above skirting</li> </ul>                                  |  |  |  |
| External dimensions   | • 30mm x 15mm (w x h)   |  |  |  |
| Таре                  | <ul> <li>Foam backed 1mm thick</li> <li>Effective on clean dry surfaces</li> <li>Caution, can spoil surfaces on removal</li> </ul>    |  |  |  |
| Paintable             | • Scuff using gentle abrasive such as sandpaper, so paint keys for best results   |  |  |  |
| Weight                | • 0.115 kg per metre  |  |  |  |
| Packaging             | Each length supplied with removable film cover  |  |  |  |
| Capacity              | • If containing 240v cables leave 45% of internal capacity for air circulation  |  |  |  |
| Quality approvals     | • BS EN 50085 - 1:2005 Part 1 SGS Registration ELS 185841/2/C/AB/16   |  |  |  |
|                       |   |  |  |  |